

FLY FANS / AIR CURTAINS



STANDARD FEATURES

- ◆ ¾ hp motors
- ◆ Galvanized steel fan wheels & housings
- ◆ Aluminum airfoil shaped directional vanes
- ◆ Aluminum base frame
- ◆ White aluminum housing
- ◆ Keyhole slots in backplate for quick wall mounting
- ◆ Licensed to bear AMCA Air Performance Seal
- ◆ UL Listed (United States & Canada)
- ◆ Five year parts warranty
- ◆ Crafted with Pride in the USA

MODEL	BERNER MODEL	Nozzle Width (in)	Max. Velocity (fpm)	Avg. Outlet Velocity (fpm)†	Air Volume‡ (scfm)	# Motor(s) @ hp	Power Rating (kW)	Outlet Velocity Unif. (%)	# Fans	Net Wgt. (lbs)	Ship Wgt. (lbs)
SERVICE ENTRY MODELS											
ASR1036AA	SCH07-1036A	36"	5917	2011	1760	1 @ ¾	.67	86.0	2	50	69
ASR1042AA	SCH07-1042A	42"	4418	1716	1752	1 @ ¾	.75	79.0	2	52	78
ASR1048AA	SCH07-1048A	48"	3815	1504	1882	1 @ ¾	.73	55.0	2	53	80

Door Switch


9503SD020-P

Each switch is suitable for single phase power only and max. amp draw of 20 amps. 120/208/240V

MOTOR VOLTAGES/AMP DRAWS			
Horsepower	3/4		
Speed	1		
Volts	120		
Phase	1		
Hertz**	50/60		
Amps per Motor	7.5		

**Operation at 50 Hz will generate approximately a 17% reduction in performance.

AMCA Seal applies to air performance only.



Berner International Corporation certifies that the air curtains shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and comply with the

Program.

Rated data shown is for base unheated units.