

HIGH TEMP ACCESS DOORS (SANDWICH STYLE)



- HI-TEMP ACCESS DOOR IS SOLID, LEAK RESISTANT AND CONSISTS OF TWO LAYERS OF STAMPED, HOT DIPPED GALVANIZED STEEL AND ONE 16 GAUGE BLACK IRON BACKING PLATE
- HI-TEMPERATURE CERAMIC FIBER GASKET (2300°F, 1260°C MAX-MEETS NFPA 96 STANDARDS) IS PERMANENTLY BONDED TO THE OUTSIDE PANEL OF THE ACCESS DOOR TO ELIMINATE LEAKAGE
- ZINC PLATED CONICAL SPRINGS ARE INSTALLED, BETWEEN THE INNER AND OUTER PLATES, TO FACILITATE OPENING
- ZINC COATED WING NUTS ARE EASILY TURNED BY HAND
- NO MEASURING (SELF-ADHESIVE TEMPLATE PROVIDED)

ACCESS DOORS	
MODEL #	CUT OUT SIZE (ROUNDED EDGES)
22-8X4	ACCESS PANEL 8" x 4"
22-10X6	ACCESS PANEL 10" x 6" **
22-12X8	ACCESS PANEL 12" x 8" **
22-16X12	ACCESS PANEL 16" x 12"
22-18X14	ACCESS PANEL 18" x 14" **

****ACCESS DOORS WITH 6" MOUNTING STUDS**

